



## DIN 2527 - PN10 CIEGA

EN 1092-1-05 PN10

Acero Inoxidable EN 1.4404/316L

Código		DN	Brida			Tornillo			Peso kg/u.
AIISI 304L	AIISI 316L		D	b	k	Cant.	Rosca	d2	
342BC1015	344BC1015	15	95	(16) 14	65	4	M12	14	0,72
342BC1020	344BC1020	20	105	(18) 16	75	4	M12	14	1,01
342BC1025	344BC1025	25	115	(18) 16	85	4	M12	14	1,23
342BC1032	344BC1032	32	140	(18) 16	100	4	M16	18	1,80
342BC1040	344BC1040	40	150	(18) 16	110	4	M16	18	2,09
342BC1050	344BC1050	50	165	18	125	4	M16	18	2,88
342BC1065	344BC1065	65	185	18	145	4	M16	18	3,66
342BC1080	344BC1080	80	200	20	160	8	M16	18	4,77
342BC1100	344BC1100	100	220	20	180	8	M16	18	5,65
342BC1125	344BC1125	125	250	22	210	8	M16	18	8,42
342BC1150	344BC1150	150	285	22	240	8	M20	22	10,40
342BC1200	344BC1200	200	340	24	295	8	M20	22	16,50
342BC1250	344BC1250	250	395	26	350	12	M20	22	24,00
342BC1300	344BC1300	300	445	26	400	12	M20	22	30,90
342BC1350	344BC1350	350	505	26	460	16	M20	22	39,65
342BC1400	344BC1400	400	565	26	515	16	M24	26	49,40
342BC1450	344BC1450	450	615	28	565	20	M24	26	62,96
342BC1500	344BC1500	500	670	28	620	20	M24	26	75,16
342BC1600	344BC1600	600	780	30	725	20	M27	30	124,00
342BC1700	344BC1700	700	895	32	840	24	M27	30	183,00

(\*) Medidas entre parentesis según norma EN1092-1-05 PN10