


Gerade Anschweißverschraubungen
Straight welding connectors
Racores para soldar rectos

GAS-..L/S

Type	Mat.-Nr.	Serie	PN	D1	D7	L1	L6	L8	SW1	SW2	g/Stk
GAS-06L	708.1400.060.20	L	315	6	10.0	29.0	14.0	7.0	12	14	25
GAS-08L	708.1400.080.20	L	315	8	12.0	31.0	16.0	8.0	14	17	36
GAS-10L	708.1400.100.20	L	315	10	14.0	33.0	18.0	8.0	17	19	47
GAS-12L	708.1400.120.20	L	315	12	16.0	33.0	18.0	8.0	19	22	55
GAS-15L	708.1400.150.20	L	315	15	19.0	37.0	22.0	10.0	22	27	90
GAS-18L	708.1400.180.20	L	315	18	22.0	40.0	23.5	10.0	27	32	130
GAS-22L	708.1400.220.20	L	160	22	27.0	45.0	28.5	12.0	32	36	190
GAS-28L	708.1400.280.20	L	160	28	32.0	47.0	30.5	12.0	41	41	270
GAS-35L	708.1400.350.20	L	160	35	40.0	54.0	32.5	14.0	46	50	395
GAS-42L	708.1400.420.20	L	160	42	46.0	58.0	35.0	16.0	55	60	585
GAS-06S	708.1400.060.30	S	630	6	11.0	34.0	19.0	7.0	14	17	38
GAS-08S	708.1400.080.30	S	630	8	13.0	36.0	21.0	8.0	17	19	54
GAS-10S	708.1400.100.30	S	630	10	15.0	39.0	22.5	8.0	19	22	70
GAS-12S	708.1400.120.30	S	630	12	17.0	41.0	24.5	10.0	22	24	125
GAS-14S	708.1400.140.30	S	630	14	19.0	45.0	27.0	10.0	24	27	140
GAS-16S	708.1400.160.30	S	400	16	21.0	45.0	26.5	10.0	27	30	156
GAS-20S	708.1400.200.30	S	400	20	26.0	51.0	29.5	12.0	32	36	240
GAS-25S	708.1400.250.30	S	400	25	31.0	56.0	32.0	12.0	41	46	460
GAS-30S	708.1400.300.30	S	400	30	36.0	62.0	35.5	14.0	46	50	555
GAS-38S	708.1400.380.30	S	315	38	44.0	69.0	38.0	16.0	55	60	786

Baumaße sind Ungefährmaße bei angezogener Überwurfmutter.

Sizes are approximate dimensions at tightened nut.

Las medidas son aproximadas con la tuerca de unión apretada.



LEHENGOMAK, S. A.