


Schneidringverschraubung Cutting Ring Fitting

Racor de anillo cortante

Meßanschluß für 24° Konen

Test point gauge for 24° taper

Conexión de medición para conos de 24°



EMV-..L/S

Type	Mat.-Nr.	Serie	PN	D1	M	H	SW1
▼ EMV-06L	708.0243.060.20	L	315	6	12x1.5	64.0	17
▼ EMV-08L	708.0243.080.20	L	315	8	14x1.5	64.0	17
▼ EMV-10L	708.0243.100.20	L	315	10	16x1.5	65.0	19
▼ EMV-12L	708.0243.120.20	L	315	12	18x1.5	65.0	22
EMV-15L	708.0243.150.20	L	315	15	22x1.5	52.0	27
EMV-18L	708.0243.180.20	L	315	18	26x1.5	55.0	32
EMV-22L	708.0243.220.20	L	160	22	30x2.0	55.0	36
EMV-28L	708.0243.280.20	L	160	28	36x2.0	55.0	41
EMV-35L	708.0243.350.20	L	160	35	45x2.0	57.0	50
EMV-42L	708.0243.420.20	L	160	42	52x2.0	57.0	60
▼ EMV-06S	708.0243.060.30	S	630	6	14x1.5	64.0	17
▼ EMV-08S	708.0243.080.30	S	630	8	16x1.5	65.0	19
▼ EMV-10S	708.0243.100.30	S	630	10	18x1.5	65.0	22
▼ EMV-12S	708.0243.120.30	S	630	12	20x1.5	68.0	24
▼ EMV-14S	708.0243.140.30	S	630	14	22x1.5	52.0	27
EMV-16S	708.0243.160.30	S	400	16	24x1.5	52.0	30
EMV-20S	708.0243.200.30	S	400	20	30x2.0	57.0	36
EMV-25S	708.0243.250.30	S	400	25	36x2.0	58.0	46
EMV-30S	708.0243.300.30	S	400	30	42x2.0	60.0	50
EMV-38S	708.0243.380.30	S	315	38	52x2.0	62.0	60

10



LEHENGOMAK, S. A.

▼=Ausführung mit Dichtkegel

▼=Version with taper

▼=Versión con junta cónica