

### Einstellbare Manometer-Anschlußstutzen



Innengewinde: Whitworth-Rohrgewinde - zylindrisch

### Adjustable manometer couplings

Female thread: BSP thread - parallel

### Racores para manómetro ajustables

Rosca de conexión: Rosca Witworth para tubos - cilíndrica



## EMAS-..LR/SR

Type	Mat.-Nr.	Serie	PN	D1	G	H	L1	SW1	SW2	g/Stk
EMAS-06LR 1.4	708.0235.110.20	L	315	6	1/4	4.5	38.0	14	19	46
EMAS-08LR 1.4	708.0235.170.20	L	315	8	1/4	4.5	38.0	17	19	53
EMAS-10LR 1.4	708.0235.270.20	L	315	10	1/4	4.5	39.5	19	19	62
EMAS-12LR 1.4	708.0235.380.20	L	315	12	1/4	4.5	40.5	22	19	70
EMAS-06SR 1.2	708.0235.125.30	S	630	6	1/2	5.0	48.0	17	27	105
EMAS-08SR 1.2	708.0235.185.30	S	630	8	1/2	5.0	48.0	19	27	107
EMAS-10SR 1.2	708.0235.285.30	S	630	10	1/2	5.0	50.0	22	27	125
EMAS-12SR 1.2	708.0235.400.30	S	630	12	1/2	5.0	47.5	24	27	134

Baumaße sind Ungefährmaße bei angezogener Überwurfmutter.

Sizes are approximate dimensions at tightened nut.

Las medidas son aproximadas con la tuerca de unión apretada.

Mit Dichtkantenring.

With seal-edgering.

Con anillo con borde de obturación.



LEHENGOMAK, S. A.