

Manometer- Anschlußverschraubungen


Innengewinde: Whitworth-Rohrgewinde - zylindrisch

Manometer couplings

Female thread: BSP thread - parallel

Racores para manómetro

Rosca de conexión: Rosca Witworth para tubos - cilíndrica



MAV-..LR/SR

Type	Mat.-Nr.	Serie	PN	D1	G	H	L1	L7	SW1	SW2	g/Stk
MAV-06LR 1.4	708.0230.110.20	L	315	6	1/4	4.5	37.0	22.0	14	19	46
MAV-08LR 1.4	708.0230.170.20	L	315	8	1/4	4.5	37.0	22.0	17	19	53
MAV-10LR 1.4	708.0230.270.20	L	315	10	1/4	4.5	38.0	23.0	19	19	62
MAV-12LR 1.4	708.0230.380.20	L	315	12	1/4	4.5	38.0	23.0	22	19	65
MAV-12LR 1.2	708.0230.400.20	L	315	12	1/2	4.5	44.0	30.0	22	27	105
MAV-06SR 1.2	708.0230.125.30	S	630	6	1/2	5.0	46.0	31.0	17	27	110
MAV-08SR 1.2	708.0230.185.30	S	630	8	1/2	5.0	46.0	31.0	19	27	115
MAV-10SR 1.2	708.0230.285.30	S	630	10	1/2	5.0	47.0	30.5	22	27	120
MAV-12SR 1.2	708.0230.400.30	S	630	12	1/2	5.0	48.0	32.0	24	27	136

Baumaße sind Ungefährmaße bei angezogener Überwurfmutter.

Sizes are approximate dimensions at tightened nut.

Las medidas son aproximadas con la tuerca de unión apretada.

Mit Dichtkantening.

With seal-edge ring.

Con anillo con borde de obturación.



LEHENGOMAK, S.A.