


Special couplings

Quick release couplings CFPV series

So

LEHENGOAK, S.A.

- Connection system: pushing the male coupling
- Disconnection system: pulling the male coupling
- Shut off system: poppet valve
- Connectability: without pressure
- Disconnection under pressure: for emergency operation only
- Interchangeability: according to ISO 7241-1 part A standard
- Balls bearing latching system
- Guidevalve with mechanical backstop
- Suitable for rigid tubes or distributors
- Breakaway feature
- 3/8" and 3/4" size



- · Cast iron manifolds
- Equipped with 2 Push-Pull couplings female part
- Provided of internal lines purposely designed to minimize pressure drops
- To be assembled on the valve by fixing screws
- Yellow zinc plating surface protection







Series 4DCPV



• Connection system: pushing the male coupling • Disconnection system: pulling the male coupling

Cartridge coupling to be integrated

in suitable valves

- or by distributor lever
- Shut-off system: poppet valve
- Connectability: both male and female couplings under pressure (one step connection)
- Disconnection under pressure: in two steps
- Interchangeability: according to ISO 7241-1 part A standard
- Balls-bearing latching system
- Guidevalve with mechanical backstop
- Cartridge design

►

- To be completely integrated in the distributor
- Breakaway feature
- Internal mechanical block patented
- Backward internal microvalve for clean oil drainage