

Schneidringverschraubung Cutting Ring Fitting

Racor de anillo cortante

T-Einschraubverschraubungen

Einschraubgewinde: Whitworth-Rohrgewinde - kegelig


Equal tees, male

Stud thread: BSP thread - taper

Racores para roscar T

Rosca de conexión: Rosca Whitworth para tubos - cónica

TEV-..LRK/SRK



Type	Mat.-Nr.	Serie	PN	D1	R	L4	L5	L6	SW1	SW3	g/Stk
TEV-04LLRK 1.8	708.3701.040.10	LL	100	4	1/8	21.0	17.0	11.0	10	9	26
TEV-06LLRK 1.8	708.3701.100.10	LL	100	6	1/8	21.0	17.0	9.5	12	9	36
TEV-08LLRK 1.8	708.3701.160.10	LL	100	8	1/8	23.0	20.0	11.5	14	12	42
TEV-06LRK 1.8	708.3701.100.20	L	315	6	1/8	27.0	20.0	12.0	14	12	52
TEV-06LRK 1.4	708.3701.110.20	L	315	6	1/4	29.0	26.0	14.0	14	12	
TEV-08LRK 1.4	708.3701.170.20	L	315	8	1/4	29.0	26.0	14.0	17	12	72
TEV-10LRK 1.4	708.3701.270.20	L	315	10	1/4	30.0	27.0	15.0	19	14	98
TEV-10LRK 3.8	708.3701.280.20	L	315	10	3/8	30.0	27.0	15.0	19	17	
TEV-12LRK 3.8	708.3701.390.20	L	315	12	3/8	32.0	28.0	17.0	22	17	139
TEV-12LRK 1.2	708.3701.400.20	L	315	12	1/2	38.0	24.0	20.5	22	17	
TEV-15LRK 1.2	708.3701.534.20	L	315	15	1/2	36.0	34.0	21.0	27	19	201
TEV-18LRK 1.2	708.3701.646.20	L	315	18	1/2	40.0	36.0	23.5	32	24	296
TEV-06SRK 1.4	708.3701.110.30	S	400	6	1/4	31.0	26.0	16.0	17	12	100
TEV-08SRK 1.4	708.3701.170.30	S	400	8	1/4	32.0	27.0	17.0	19	14	113
TEV-10SRK 3.8	708.3701.280.30	S	400	10	3/8	34.0	28.0	17.5	22	17	166
TEV-12SRK 3.8	708.3701.390.30	S	400	12	3/8	38.0	28.0	21.5	24	17	187
TEV-12SRK 1.2	708.3701.400.30	S	400	12	1/2	40.0	32.0	22.0	27	19	
TEV-14SRK 1.2	708.3701.504.30	S	400	14	1/2	40.0	32.0	22.0	27	19	238
TEV-16SRK 1.2	708.3701.566.30	S	400	16	1/2	43.0	32.0	24.5	30	24	339

Baumaße sind Ungefährmaße bei angezogener Überwurfmutter.

Sizes are approximate dimensions at tightened nut.

Las medidas son aproximadas con la tuerca de unión apretada.

10



LEHENGOTAK, S. A.