

Schneidringverschraubung Cutting Ring Fitting

Racor de anillo cortante

L-Einschraubverschraubungen


Einschraubgewinde: Whitworth-Rohrgewinde - zylindrisch

Male stud tee-stud barrels

Stud thread: BSP thread - parallel

Racores para roscar L

Rosca de conexión: Rosca Whitworth para tubos - cilíndrica



LEV-..LR/SR

Type	Mat.-Nr.	Serie	PN	D1	G	L5	L6	SW1	SW3	g/Stk
LEV-22LR 3.4	708.3712.708.20	L	160	22	3/4	44.0	26.0	36	27	371
LEV-28LR 1.1	708.3712.850.20	L	160	28	1	47.0	30.0	41	36	544
LEV-35LR 5.4	708.3712.944.20	L	160	35	1 1/4	56.0	34.0	50	41	844
LEV-42LR 3.2	708.3712.992.20	L	160	42	1 1/2	63.0	39.0	60	50	1240
LEV-20SR 3.4	708.3712.704.30	S	400	20	3/4	48.0	26.0	36	27	479
LEV-25SR 1.1	708.3712.810.30	S	400	25	1	54.0	30.0	46	36	891
LEV-30SR 5.4	708.3712.902.30	S	400	30	1 1/4	62.0	34.0	50	41	1227
LEV-38SR 3.2	708.3712.953.30	S	315	38	1 1/2	72.0	39.0	60	50	1712

Baumaße sind Ungefährmaße bei angezogener Überwurfmutter.

Sizes are approximate dimensions at tightened nut.

Las medidas son aproximadas con la tuerca de unión apretada.

Abdichtung durch Dichtkante Form B.

Sealing by stud face form B

Cierre hermético con junta de obturación forma B.



LEHENGOMK, S. A.