

Schneidringverschraubung Cutting Ring Fitting

Racor de anillo cortante

L-Einschraubverschraubungen

Einschraubgewinde: Metrisches Gewinde - zylindrisch


Male stud tee-stud barrels

Stud thread: metric - parallel

Racores para roscar L

Rosca de conexión: Rosca métrica - cilíndrica

LEV-..LM/SM



Type	Mat.-Nr.	Serie	PN	D1	M	L5	L6	SW1	SW3	g/Stk
LEV-22LM 26x1,5	708.3753.635.20	L	160	22	26x1.5	44.0	26.0	36	27	371
LEV-28LM 33x2,0	708.3753.650.20	L	160	28	33x2.0	47.0	30.0	41	36	544
LEV-35LM 42x2,0	708.3753.944.20	L	160	35	42x2.0	56.0	34.0	50	41	844
LEV-42LM 48x2,0	708.3753.992.20	L	160	42	48x2.0	63.0	39.0	60	50	1240
LEV-20SM 27x2,0	708.3753.704.30	S	400	20	27x2.0	48.0	26.0	36	27	479
LEV-25SM 33x2,0	708.3753.745.30	S	400	25	33x2.0	54.0	30.0	46	36	891
LEV-30SM 42x2,0	708.3753.902.30	S	400	30	42x2.0	62.0	34.0	50	41	1227
LEV-38SM 48x2,0	708.3753.953.30	S	400	38	48x2.0	72.0	39.0	60	50	1712

Baumaße sind Ungefährmaße bei angezogener Überwurfmutter.

Sizes are approximate dimensions at tightened nut.

Las medidas son aproximadas con la tuerca de unión apretada.

Abdichtung durch Dichtkante Form B.

Sealing by stud face form B

Cierre hermético con junta de obturación forma B.



LEHENGOTAK, S. A.