

Schneidringverschraubung Cutting Ring Fitting

Racor de anillo cortante

L-Einschraubverschraubungen

Einschraubgewinde: Whitworth-Rohrgewinde - kegelig


Male stud tee-stud barrels

Stud thread: BSP thread - taper

Racores para roscar L

Rosca de conexión: Rosca Whitworth para tubos - cónica

LEV-..LRK/SRK



Type	Mat.-Nr.	Serie	PN	D1	R	L4	L5	SW1	SW3	g/Stk
LEV-04LLRK 1.8	708.3711.040.10	LL	100	4	1/8	17.0	21.0	10	9	26
LEV-06LLRK 1.8	708.3711.100.10	LL	100	6	1/8	17.0	21.0	12	9	36
LEV-08LLRK 1.8	708.3711.161.10	LL	100	8	1/8	20.0	23.0	14	12	42
LEV-06LRK 1.8	708.3711.100.20	L	315	6	1/8	20.0	27.0	14	12	53
LEV-06LRK 1.4	708.3711.111.20	L	315	6	1/4	26.0	27.0	14	12	
LEV-08LRK 1.4	708.3711.170.20	L	315	8	1/4	26.0	29.0	17	12	75
LEV-10LRK 1.4	708.3711.270.20	L	315	10	1/4	27.0	30.0	19	14	100
LEV-12LRK 3.8	708.3711.390.20	L	315	12	3/8	28.0	32.0	22	17	120
LEV-15LRK 1.2	708.3711.534.20	L	315	15	1/2	34.0	36.0	27	19	167
LEV-18LRK 1.2	708.3711.646.20	L	315	18	1/2	36.0	40.0	32	24	296
LEV-06SRK 1.4	708.3711.111.30	S	400	6	1/4	26.0	31.0	17	12	97
LEV-08SRK 1.4	708.3711.170.30	S	400	8	1/4	27.0	32.0	19	14	128
LEV-10SRK 3.8	708.3711.280.30	S	400	10	3/8	28.0	34.0	22	17	172
LEV-12SRK 3.8	708.3711.390.30	S	400	12	3/8	28.0	38.0	24	17	244
LEV-14SRK 1.2	708.3711.504.30	S	400	14	1/2	32.0	40.0	27	19	240
LEV-16SRK 1.2	708.3711.566.30	S	400	16	1/2	32.0	43.0	30	24	320

Baumaße sind Ungefährmaße bei angezogener Überwurfmutter.

Sizes are approximate dimensions at tightened nut.

Las medidas son aproximadas con la tuerca de unión apretada.



LEHENGOTAK, S. A.