

Gerade Aufschraubverschraubungen


Innengewinde: Whitworth-Rohrgewinde - zylindrisch

Straight connectors, female

Female thread: BSP thread - parallel

Racores atornillables rectos

Rosca interior: Rosca Witworth para tubos - cilíndrica

GAV-..LR


Type	Mat.-Nr.	Serie	PN	D1	G	L1	L7	SW1	SW2	g/Stk
GAV-06LR 1.8	708.1201.100.20	L	315	6	1/8	34.0	19.0	14	14	27
GAV-06LR 1.4	708.1201.110.20	L	315	6	1/4	39.0	24.0	19	14	48
GAV-08LR 1.4	708.1201.170.20	L	315	8	1/4	39.0	24.0	19	17	50
GAV-08LR 3.8	708.1201.180.20	L	315	8	3/8	40.0	25.0	22	17	78
GAV-08LR 1.2	708.1201.185.20	L	315	8	1/2	42.0	28.0	27	17	84
GAV-10LR 1.4	708.1201.270.20	L	315	10	1/4	40.0	25.0	19	19	60
GAV-10LR 3.8	708.1201.280.20	L	315	10	3/8	41.0	26.0	22	19	68
GAV-10LR 1.2	708.1201.285.20	L	315	10	1/2	41.0	26.0	27	19	102
GAV-12LR 1.4	708.1201.380.20	L	315	12	1/4	40.0	25.0	19	22	68
GAV-12LR 3.8	708.1201.390.20	L	315	12	3/8	41.0	26.0	22	22	88
GAV-12LR 1.2	708.1201.400.20	L	315	12	1/2	46.0	29.0	27	22	106
GAV-15LR 3.8	708.1201.532.20	L	315	15	3/8	42.0	27.0	24	27	114
GAV-15LR 1.2	708.1201.534.20	L	315	15	1/2	46.0	31.0	27	27	113
GAV-18LR 3.8	708.1201.644.20	L	315	18	3/8	44.0	27.5	27	32	168
GAV-18LR 1.2	708.1201.646.20	L	315	18	1/2	47.0	30.5	27	32	151
GAV-22LR 3.4	708.1201.768.20	L	160	22	3/4	52.0	35.5	36	36	270
GAV-28LR 1.1	708.1201.850.20	L	160	28	1	55.0	38.0	41	41	311
GAV-35LR 5.4	708.1201.944.20	L	160	35	1 1/4	63.0	41.0	55	50	588
GAV-42LR 3.2	708.1201.992.20	L	160	42	1 1/2	65.0	42.5	60	60	760

Baumaße sind Ungefährmaße bei angezogener Überwurfmutter.

Sizes are approximate dimensions at tightened nut.

Las medidas son aproximadas con la tuerca de unión apretada.



LEHENGOMAK, S. A.