

Gerade Aufschraubverschraubungen


Innengewinde: Whitworth-Rohrgewinde - zylindrisch

Straight connectors, female

Female thread: BSP thread - parallel

Racores atornillables rectos

Rosca interior: Rosca Witworth para tubos - cilíndrica



GAV-..SR

| Type | Mat.-Nr. | Serie | PN | D1 | G | L1 | L2 | SW1 | SW2 | g/Stk |
|--------------|-----------------|-------|-----|----|-------|------|------|-----|-----|-------|
| GAV-06SR 1.8 | 708.1201.100.30 | S | 630 | 6 | 1/8 | 36.0 | 21.0 | 17 | 17 | 50 |
| GAV-06SR 1.4 | 708.1201.110.30 | S | 630 | 6 | 1/4 | 41.0 | 26.0 | 19 | 17 | 49 |
| GAV-08SR 1.4 | 708.1201.170.30 | S | 630 | 8 | 1/4 | 41.0 | 26.0 | 19 | 19 | 59 |
| GAV-10SR 1.4 | 708.1201.270.30 | S | 630 | 10 | 1/4 | 43.0 | 26.5 | 22 | 22 | 114 |
| GAV-10SR 3.8 | 708.1201.280.30 | S | 630 | 10 | 3/8 | 43.0 | 26.5 | 24 | 22 | 100 |
| GAV-12SR 1.4 | 708.1201.380.30 | S | 630 | 12 | 1/4 | 45.0 | 27.0 | 22 | 24 | 106 |
| GAV-12SR 3.8 | 708.1201.390.30 | S | 630 | 12 | 3/8 | 43.0 | 26.5 | 24 | 24 | 112 |
| GAV-12SR 1.2 | 708.1201.400.30 | S | 630 | 12 | 1/2 | 47.0 | 29.5 | 27 | 24 | 122 |
| GAV-14SR 1.2 | 708.1201.504.30 | S | 630 | 14 | 1/2 | 50.0 | 32.0 | 27 | 27 | 148 |
| GAV-16SR 1.2 | 708.1201.566.30 | S | 400 | 16 | 1/2 | 50.0 | 31.5 | 27 | 30 | 175 |
| GAV-20SR 3.8 | 708.1201.703.30 | S | 400 | 20 | 3/8 | 49.0 | 27.5 | 32 | 36 | 245 |
| GAV-20SR 1.2 | 708.1201.706.30 | S | 400 | 20 | 1/2 | 52.0 | 30.5 | 32 | 36 | 248 |
| GAV-20SR 3.4 | 708.1201.708.30 | S | 400 | 20 | 3/4 | 56.0 | 34.5 | 36 | 36 | 300 |
| GAV-25SR 1.1 | 708.1201.810.30 | S | 400 | 25 | 1 | 62.0 | 37.5 | 41 | 46 | 466 |
| GAV-30SR 5.4 | 708.1201.902.30 | S | 400 | 30 | 1 1/4 | 69.0 | 42.0 | 55 | 50 | 719 |
| GAV-38SR 3.2 | 708.1201.953.30 | S | 315 | 38 | 1 1/2 | 74.0 | 43.5 | 60 | 60 | 890 |

Baumaße sind Ungefährmaße bei angezogener Überwurfmutter.

Sizes are approximate dimensions at tightened nut.

Las medidas son aproximadas con la tuerca de unión apretada.



LEHENGOMAK, S. A.