

Schneidringverschraubung Cutting Ring Fitting

Racor de anillo cortante

Gerade Aufschraubverschraubungen


Innengewinde: Metrisches Gewinde - zylindrisch

Straight connectors, female

Female thread: Metric thread - parallel

Racores atornillables rectos

Rosca interior: Rosca métrica - cilíndrica



GAV-..LM/SM

Type	Mat.-Nr.	Serie	PN	D1	M	L1	L7	SW1	SW2	g/Stk
GAV-06LM 10x1,0	708.1204.180.20	L	315	6	10x1.0	34.0	19.5	14	14	26
GAV-08LM 12x1,5	708.1204.240.20	L	315	8	12x1.5	39.0	24.0	17	17	50
GAV-10LM 14x1,5	708.1204.280.20	L	315	10	14x1.5	40.0	25.0	19	19	50
GAV-12LM 16x1,5	708.1204.330.20	L	315	12	16x1.5	41.0	26.0	22	22	90
GAV-12LM 18x1,5	708.1204.333.20	L	315	12	18x1.5	43.0	28.0	24	22	95
GAV-12LM 20x1,5	708.1204.335.20	L	315	12	20x1.5	43.0	28.0	27	22	110
GAV-15LM 18x1,5	708.1204.390.20	L	315	15	18x1.5	43.0	28.0	24	27	115
GAV-18LM 22x1,5	708.1204.460.20	L	315	18	22x1.5	46.0	29.5	30	32	157
GAV-22LM 26x1,5	708.1204.535.20	L	160	22	26x1.5	51.0	34.5	32	36	215
GAV-28LM 33x2,0	708.1204.570.20	L	160	28	33x2.0	54.0	37.5	41	41	320
GAV-35LM 42x2,0	708.1204.600.20	L	160	35	42x2.0	62.0	40.5	55	50	620
GAV-42LM 48x2,0	708.1204.992.20	L	160	42	48x2.0	65.0	42.5	60	60	780
GAV-06SM 12x1,5	708.1204.190.30	S	630	6	12x1.5	41.0	26.0	17	17	54
GAV-08SM 14x1,5	708.1204.198.30	S	630	8	14x1.5	41.0	26.0	19	19	69
GAV-10SM 16x1,5	708.1204.285.30	S	630	10	16x1.5	43.0	26.5	22	22	102
GAV-12SM 18x1,5	708.1204.333.30	S	630	12	18x1.5	44.0	27.5	24	24	110
GAV-12SM 20x1,5	708.1204.335.30	S	630	12	20x1.5	46.0	29.5	27	24	125
GAV-14SM 20x1,5	708.1204.382.30	S	630	14	20x1.5	49.0	31.0	27	27	148
GAV-16SM 20x1,5	708.1204.410.30	S	400	16	22x1.5	49.0	30.5	30	30	175
GAV-20SM 27x2,0	708.1204.506.30	S	400	20	27x2.0	56.0	34.5	36	36	307
GAV-25SM 33x2,0	708.1204.550.30	S	400	25	33x2.0	61.0	37.0	41	46	466
GAV-30SM 42x2,0	708.1204.590.30	S	400	30	42x2.0	68.0	41.5	55	50	765
GAV-38SM 48x2,0	708.1204.954.30	S	315	38	48x2.0	74.0	43.0	60	60	920

Baumaße sind Ungefährmaße bei angezogener Überwurfmutter.

Sizes are approximate dimensions at tightened nut.

Las medidas son aproximadas con la tuerca de unión apretada.



LEHENGOMAK, S. A.