


Gerade Verschraubungen
Straight fittings
Racores rectos

GV-..L/S

Type	Mat.-Nr.	Serie	PN	D1	L1	L7	SW1	SW2	g/Stk
GV-04LL	708.1020.040.10	LL	100	4	31.0	12.0	10	9	15
GV-06LL	708.1020.060.10	LL	100	6	32.0	9.0	12	11	20
GV-08LL	708.1020.080.10	LL	100	8	35.0	12.0	14	12	26
GV-10LL	708.1020.100.10	LL	100	10	36.0	12.0	17	14	29
GV-12LL	708.1020.120.10	LL	100	12	35.0	11.0	19	17	31
GV-06L	708.1020.060.20	L	315	6	39.0	10.0	14	12	35
GV-08L	708.1020.080.20	L	315	8	40.0	11.0	17	14	50
GV-10L	708.1020.100.20	L	315	10	42.0	13.0	19	17	65
GV-12L	708.1020.120.20	L	315	12	43.0	14.0	22	19	85
GV-15L	708.1020.150.20	L	315	15	46.0	16.0	27	24	412
GV-18L	708.1020.180.20	L	315	18	48.0	16.0	32	27	201
GV-22L	708.1020.220.20	L	160	22	52.0	20.0	36	32	274
GV-28L	708.1020.280.20	L	160	28	54.0	21.0	41	41	347
GV-35L	708.1020.350.20	L	160	35	63.0	20.0	50	46	543
GV-42L	708.1020.420.20	L	160	42	66.0	21.0	60	55	790
GV-06S	708.1020.060.30	S	630	6	45.0	16.0	17	14	65
GV-08S	708.1020.080.30	S	630	8	47.0	18.0	19	17	83
GV-10S	708.1020.100.30	S	630	10	49.0	17.0	22	19	110
GV-12S	708.1020.120.30	S	630	12	51.0	19.0	24	22	135
GV-14S	708.1020.140.30	S	630	14	57.0	22.0	27	24	187
GV-16S	708.1020.160.30	S	400	16	57.0	21.0	30	27	229
GV-20S	708.1020.200.30	S	400	20	66.0	23.0	36	32	350
GV-25S	708.1020.250.30	S	400	25	74.0	26.0	46	41	672
GV-30S	708.1020.300.30	S	400	30	80.0	27.0	50	46	821
GV-38S	708.1020.380.30	S	315	38	90.0	29.0	60	55	1215

Baumaße sind Ungefährmaße bei angezogener Überwurfmutter.

Sizes are approximate dimensions at tightened nut.

Las medidas son aproximadas con la tuerca de unión apretada.