


Schneidringverschraubung Cutting Ring Fitting

Racor de anillo cortante

Winkel-Schottverschraubungen

Bulkhead elbow couplings

Racores pasatabiques a codo de 90°



WSV-..L/S

Type	Mat.-Nr.	Serie	PN	D1	D7	M	L5	L6	L7	SW1	SW2	SW3	g/Stk
WSV-06L	708.2700.060.20	L	315	6	17.0	12x1.5	27.0	14.0	42.0	12	17	14	73
WSV-08L	708.2700.080.20	L	315	8	19.0	14x1.5	29.0	17.0	42.0	12	19	17	92
WSV-10L	708.2700.100.20	L	315	10	22.0	16x1.5	30.0	18.0	43.0	14	22	19	172
WSV-12L	708.2700.120.20	L	315	12	24.0	18x1.5	32.0	20.0	44.0	17	24	22	215
WSV-15L	708.2700.150.20	L	315	15	27.0	22x1.5	36.0	23.0	46.0	19	30	27	345
WSV-18L	708.2700.180.20	L	315	18	32.0	26x1.5	40.0	24.0	49.0	24	36	32	380
WSV-22L	708.2700.220.20	L	160	22	36.0	30x2.0	44.0	30.0	51.0	27	41	36	490
WSV-28L	708.2700.280.20	L	160	28	42.0	36x2.0	47.0	34.0	52.0	36	46	41	678
WSV-35L	708.2700.350.20	L	160	35	50.0	45x2.0	56.0	39.0	58.0	41	55	50	1055
WSV-42L	708.2700.420.20	L	160	42	60.0	52x2.0	63.0	43.0	59.0	50	65	60	1583
WSV-06S	708.2700.060.30	S	630	6	19.0	14x1.5	31.0	17.0	44.0	12	19	17	117
WSV-08S	708.2700.080.30	S	630	8	22.0	16x1.5	32.0	18.0	44.0	14	22	19	185
WSV-10S	708.2700.100.30	S	630	10	24.0	18x1.5	34.0	20.0	46.0	17	24	22	195
WSV-12S	708.2700.120.30	S	630	12	27.0	20x1.5	38.0	21.0	47.0	17	27	24	245
WSV-14S	708.2700.140.30	S	630	14	27.0	22x1.5	40.0	23.0	50.0	19	30	27	375
WSV-16S	708.2700.160.30	S	400	16	30.0	24x1.5	43.0	24.0	50.0	24	32	30	395
WSV-20S	708.2700.200.30	S	400	20	36.0	30x2.0	48.0	30.0	55.0	27	41	36	606
WSV-25S	708.2700.250.30	S	400	25	42.0	36x2.0	54.0	34.0	59.0	36	46	46	1050
WSV-30S	708.2700.300.30	S	400	30	50.0	42x2.0	62.0	39.0	64.0	41	50	50	1360
WSV-38S	708.2700.380.30	S	315	38	60.0	52x2.0	72.0	43.0	68.0	50	65	60	2060

Baumaße sind Ungefährmaße bei angezogener Überwurfmutter.

Sizes are approximate dimensions at tightened nut.

Las medidas son aproximadas con la tuerca de unión apretada.



LEHENGOTAK, S. A.