

Schneidringverschraubung Cutting Ring Fitting

Racor de anillo cortante

Einstellbare T-Verschraubungen


Einschraubgewinde: Whitworth-Rohrgewinde - zylindrisch

Adjustable equal tees

Stud thread: BSP thread - parallel

Racores T ajustables

Rosca de conexión: Rosca Witworth para tubos - cilíndrica



ETV-..LR/SR

Type	Mat.-Nr.	Serie	PN	D1	G	L4	L5	SW1	SW2	SW3	g/Stk
ETV-06LR 1.8	708.3651.100.20	L	315	6	1/8	27.0	34.5	14	14	12	71
ETV-08LR 1.4	708.3651.170.20	L	315	8	1/4	29.0	37.0	17	19	12	106
ETV-10LR 1.4	708.3651.270.20	L	315	10	1/4	30.0	39.5	19	19	14	128
ETV-12LR 3.8	708.3651.390.20	L	315	12	3/8	32.0	41.5	22	22	17	175
ETV-15LR 1.2	708.3651.534.20	L	315	15	1/2	36.0	45.5	27	27	19	291
ETV-18LR 1.2	708.3651.646.20	L	315	18	1/2	40.0	49.5	32	27	24	427
ETV-22LR 3.4	708.3651.768.20	L	160	22	3/4	44.0	54.5	36	32	27	568
ETV-28LR 1.1	708.3651.850.20	L	160	28	1	47.0	59.0	41	41	36	792
ETV-35LR 5.4	708.3651.944.20	L	160	35	1 1/4	56.0	68.5	50	50	41	1230
ETV-42LR 3.2	708.3651.992.20	L	160	42	1 1/2	63.0	75.5	60	55	50	1671
ETV-06SR 1.4	708.3651.110.30	S	630	6	1/4	31.0	40.0	17	19	12	128
ETV-08SR 1.4	708.3651.170.30	S	630	8	1/4	32.0	42.0	19	19	14	158
ETV-10SR 3.8	708.3651.280.30	S	630	10	3/8	34.0	44.5	22	22	17	219
ETV-12SR 3.8	708.3651.390.30	S	630	12	3/8	38.0	47.5	24	22	17	277
ETV-14SR 1.2	708.3651.504.30	S	630	14	1/2	40.0	53.5	27	27	19	387
ETV-16SR 1.2	708.3651.566.30	S	400	16	1/2	43.0	54.5	30	37	24	442
ETV-20SR 3.4	708.3651.704.30	S	400	20	3/4	48.0	64.5	36	32	27	722
ETV-25SR 1.1	708.3651.810.30	S	400	25	1	54.0	72.5	46	41	36	1428
ETV-30SR 3.2	708.3651.905.30	S	400	30	1 1/2	62.0	78.5	50	50	41	1789
ETV-38SR 5.4	708.3651.954.30	S	315	38	1 1/4	72.0	89.0	60	55	50	2624

Baumaße sind Ungefährmaße bei angezogener Überwurfmutter.

Sizes are approximate dimensions at tightened nut.

Las medidas son aproximadas con la tuerca de unión apretada.

Abdichtung durch Dichtkante Form B.

Sealing by stud face form B.

Cierre hermético con junta de obturación forma B.