

Schneidringverschraubung Cutting Ring Fitting

Racor de anillo cortante

Einstellbare L-Verschraubungen

Schaft vormontiert


Adjustable male stud tee-stud barrels

with pre-installed cutting ring

Racores L ajustables

Vástago premontado

ELV-..L/S



Type	Mat.-Nr.	Serie	PN	D1	L2	L5	SW2	SW3	g/Stk
ELV-06L	708.3630.060.20	L	315	6	26.0	27.0	14	12	60
ELV-08L	708.3630.080.20	L	315	8	27.5	29.0	17	12	85
ELV-10L	708.3630.100.20	L	315	10	29.0	30.0	19	14	115
ELV-12L	708.3630.120.20	L	315	12	29.5	32.0	22	17	135
ELV-15L	708.3630.150.20	L	315	15	32.5	36.0	27	19	240
ELV-18L	708.3630.180.20	L	315	18	35.5	40.0	32	24	340
ELV-22L	708.3630.220.20	L	160	22	38.5	44.0	36	27	464
ELV-28L	708.3630.280.20	L	160	28	41.5	47.0	41	36	604
ELV-35L	708.3630.350.20	L	160	35	51.0	56.0	50	41	941
ELV-42L	708.3630.420.20	L	160	42	56.0	63.0	60	50	1433
ELV-06S	708.3630.060.30	S	630	6	27.0	31.0	17	12	100
ELV-08S	708.3630.080.30	S	630	8	27.5	32.0	19	14	125
ELV-10S	708.3630.100.30	S	630	10	30.0	34.0	22	17	175
ELV-12S	708.3630.120.30	S	630	12	30.5	38.0	24	17	205
ELV-14S	708.3630.140.30	S	630	14	34.5	40.0	27	19	285
ELV-16S	708.3630.160.30	S	400	16	36.5	43.0	30	24	375
ELV-20S	708.3630.200.30	S	400	20	44.5	48.0	36	27	590
ELV-25S	708.3630.250.30	S	400	25	50.0	54.0	46	36	1130
ELV-30S	708.3630.300.30	S	400	30	55.0	62.0	50	41	1373
ELV-38S	708.3630.380.30	S	315	38	63.0	72.0	60	50	2070

Baumaße sind Ungefährmaße bei angezogener Überwurfmutter.

Sizes are approximate dimensions at tightened nut.

Las medidas son aproximadas con la tuerca de unión apretada.



LEHENGOMAK, S. A.