

Schneidringverschraubung Cutting Ring Fitting

Racor de anillo cortante

Einstellbare L-Verschraubungen

Einschraubgewinde: Whitworth-Rohrgewinde - zylindrisch


Adjustable male stud tee-stud barrels

Stud thread: BSP thread - parallel

Racores L ajustables

Rosca de conexión: Rosca Whitworth para tubos - cilíndrica

ELV-..LR/SR



Type	Mat.-Nr.	Serie	PN	D1	G	L5	L8	SW1	SW2	SW3	g/Stk
ELV-06LR 1.8	708.3652.100.20	L	315	6	1/8	27.0	34.5	12	14	14	77
ELV-08LR 1.4	708.3652.170.20	L	315	8	1/4	29.0	37.0	12	19	17	108
ELV-10LR 1.4	708.3652.270.20	L	315	10	1/4	30.0	39.5	14	19	19	129
ELV-12LR 3.8	708.3652.390.20	L	315	12	3/8	32.0	41.5	17	22	22	174
ELV-15LR 1.2	708.3652.534.20	L	315	15	1/2	36.0	46.0	19	27	27	296
ELV-18LR 1.2	708.3652.646.20	L	315	18	1/2	40.0	49.5	24	27	32	402
ELV-22LR 3.4	708.3652.768.20	L	160	22	3/4	44.0	54.5	27	32	36	582
ELV-28LR 1.1	708.3652.850.20	L	160	28	1	47.0	59.0	36	41	41	770
ELV-35LR 5.4	708.3652.944.20	L	160	35	1 1/4	56.0	68.5	41	50	50	1193
ELV-42LR 3.2	708.3652.992.20	L	160	42	1 1/2	63.0	75.5	50	55	60	1576
ELV-06SR 1.4	708.3652.111.30	S	630	6	1/4	31.0	40.0	12	19	17	127
ELV-08SR 1.4	708.3652.170.30	S	630	8	1/4	32.0	42.0	14	19	19	160
ELV-10SR 3.8	708.3652.280.30	S	630	10	3/8	34.0	44.5	17	22	22	223
ELV-12SR 3.8	708.3652.390.30	S	630	12	3/8	38.0	47.5	17	22	24	265
ELV-14SR 1.2	708.3652.504.30	S	630	14	1/2	40.0	53.5	19	27	27	377
ELV-16SR 1.2	708.3652.566.30	S	400	16	1/2	43.0	54.5	24	37	30	461
ELV-20SR 3.4	708.3652.704.30	S	400	20	3/4	48.0	64.5	27	32	36	788
ELV-25SR 1.1	708.3652.810.30	S	400	25	1	54.0	72.5	36	41	46	1477
ELV-30SR 5.4	708.3652.902.30	S	400	30	1 1/4	62.0	78.5	41	50	50	1796
ELV-38SR 3.2	708.3652.953.30	S	315	38	1 1/2	72.0	89.0	50	55	60	2560

Baumaße sind Ungefährmaße bei angezogener Überwurfmutter.

Sizes are approximate dimensions at tightened nut.

Las medidas son aproximadas con la tuerca de unión apretada.

Abdichtung durch Dichtkante Form B.

Sealing by stud face form B.

Cierre hermético con junta de obturación forma B.



LEHENGOTAK, S. A.