

Schneidringverschraubung Cutting Ring Fitting

Racor de anillo cortante

Einstellbare L-Verschraubungen

Einschraubgewinde: Metrisches Gewinde - zylindrisch


Adjustable male stud tee-stud barrels

Stud thread: metric - parallel

Racores L ajustables

Rosca de conexión: Rosca métrica - cilíndrica

ELV-..LM/SM



Type	Mat.-Nr.	Serie	PN	D1	M	L5	L8	SW1	SW2	SW3	g/Stk
ELV-06LM 10x1,0	708.3654.180.20	L	315	6	10x1.0	27.0	34.5	12	14	14	77
ELV-08LM 12x1,5	708.3654.190.20	L	315	8	12x1.5	29.0	37.0	12	19	17	108
ELV-10LM 14x1,5	708.3654.260.20	L	315	10	14x1.5	30.0	39.5	14	19	19	129
ELV-12LM 16x1,5	708.3654.340.20	L	315	12	16x1.5	32.0	41.5	17	22	22	174
ELV-15LM 18x1,5	708.3654.532.20	L	315	15	18x1.5	36.0	45.5	19	24	27	296
ELV-18LM 22x1,5	708.3654.574.20	L	315	18	22x1.5	40.0	49.5	24	27	32	402
ELV-22LM 26x1,5	708.3654.635.20	L	160	22	26x1.5	44.0	54.5	27	32	36	582
ELV-28LM 33x2,0	708.3654.850.20	L	160	28	33x2.0	47.0	59.0	36	41	41	770
ELV-35LM 42x2,0	708.3654.944.20	L	160	35	42x2.0	56.0	68.5	41	50	50	1193
ELV-42LM 48x2,0	708.3654.992.20	L	160	42	48x2.0	63.0	75.0	50	55	60	1576
ELV-06SM 12x1,5	708.3654.195.30	S	630	6	12x1.5	31.0	40.0	12	19	17	127
ELV-08SM 14x1,5	708.3654.245.30	S	630	8	14x1.5	32.0	42.0	14	19	19	16
ELV-10SM 16x1,5	708.3654.270.30	S	630	10	16x1.5	34.0	44.5	17	22	22	223
ELV-12SM 18x1,5	708.3654.350.30	S	630	12	18x1.5	38.0	47.5	17	22	24	265
ELV-14SM 20x1,5	708.3654.504.30	S	630	14	20x1.5	40.0	53.5	19	27	27	377
ELV-16SM 22x1,5	708.3654.566.30	S	400	16	22x1.5	43.0	54.5	24	37	30	462
ELV-20SM 27x2,0	708.3654.506.30	S	400	20	27x2.0	48.0	64.5	27	32	36	788
ELV-25SM 33x2,0	708.3654.745.30	S	400	25	33x2.0	54.0	72.5	36	41	46	1477
ELV-30SM 42x2,0	708.3654.902.30	S	400	30	42x2.0	62.0	78.5	41	50	50	1796
ELV-38SM 48x2,0	708.3654.953.30	S	315	38	48x2.0	72.0	89.0	50	55	60	2560

Baumaße sind Ungefährmaße bei angezogener Überwurfmutter.

Sizes are approximate dimensions at tightened nut.

Las medidas son aproximadas con la tuerca de unión apretada.

Abdichtung durch Dichtkante Form B.

Sealing by stud face form B.

Cierre hermético con junta de obturación forma B.



LEHENGOMK, S. A.