

Einstellbare Winkelverschraubungen


Schaft vormontiert

Adjustable male stud elbows

with pre-installed cutting ring

Racores angulares ajustables

Vástago premontado


EWV-..L/S

Type	Mat.-Nr.	Serie	PN	D1	L2	L5	L7	SW2	SW3	g/Stk
EWV-06L	708.2620.060.20	L	315	6	27.0	26.0	12.0	14	12	35
EWV-08L	708.2620.080.20	L	315	8	29.0	27.5	14.0	17	12	54
EWV-10L	708.2620.100.20	L	315	10	30.0	29.0	15.0	19	14	68
EWV-12L	708.2620.120.20	L	315	12	32.0	29.5	17.0	22	17	95
EWV-15L	708.2620.150.20	L	315	15	36.0	32.5	21.0	27	19	170
EWV-18L	708.2620.180.20	L	315	18	40.0	35.5	23.5	32	24	250
EWV-22L	708.2620.220.20	L	160	22	44.0	38.5	27.5	36	27	335
EWV-28L	708.2620.280.20	L	160	28	47.0	41.5	30.5	41	36	475
EWV-35L	708.2620.350.20	L	160	35	56.0	51.0	34.5	50	41	700
EWV-42L	708.2620.420.20	L	160	42	63.0	56.0	40.0	60	50	1071
EWV-06S	708.2620.060.30	S	630	6	31.0	27.0	16.0	17	12	62
EWV-08S	708.2620.080.30	S	630	8	32.0	27.5	17.0	19	14	90
EWV-10S	708.2620.100.30	S	630	10	34.0	30.0	17.5	22	17	123
EWV-12S	708.2620.120.30	S	630	12	38.0	30.5	21.5	24	17	140
EWV-14S	708.2620.140.30	S	630	14	40.0	34.5	22.0	27	19	200
EWV-16S	708.2620.160.30	S	400	16	43.0	36.5	24.5	30	24	248
EWV-20S	708.2620.200.30	S	400	20	48.0	44.5	26.5	36	27	432
EWV-25S	708.2620.250.30	S	400	25	54.0	50.0	30.0	46	36	784
EWV-30S	708.2620.300.30	S	400	30	62.0	55.0	35.5	50	41	355
EWV-38S	708.2620.380.30	S	315	38	72.0	63.0	41.0	60	50	410

Baumaße sind Ungefährmaße bei angezogener Überwurfmutter.

Sizes are approximate dimensions at tightened nut.

Las medidas son aproximadas con la tuerca de unión apretada.


LEHENGOMAK, S. A.