

Einschraubstutzen mit Schaft


Einschraubgewinde: NPT

Stud standpipe adaptors, male

Stud thread: NPT

Racor para rosar con vástago

Rosca de conexión: NPT

ESS-..L-NPT


| Type | Mat.-Nr. | Serie | PN | D1 | NPT | L1 | SW1 | SW2 | g/Stk |
|----------------|-----------------|-------|-----|----|-------|------|-----|-----|-------|
| ESS-06LNPT 1.8 | 708.1602.100.20 | L | 315 | 6 | 1/8 | 33.0 | 11 | 14 | 26 |
| ESS-08LNPT 1.4 | 708.1602.170.20 | L | 315 | 8 | 1/4 | 40.0 | 14 | 17 | 54 |
| ESS-10LNPT 1.4 | 708.1602.270.20 | L | 315 | 10 | 1/4 | 40.5 | 14 | 19 | 47 |
| ESS-12LNPT 1.4 | 708.1602.380.20 | L | 315 | 12 | 1/4 | 40.5 | 14 | 22 | 52 |
| ESS-12LNPT 3.8 | 708.1602.390.20 | L | 315 | 12 | 3/8 | 40.5 | 19 | 22 | 70 |
| ESS-12LNPT 1.2 | 708.1602.400.20 | L | 315 | 12 | 1/2 | 45.5 | 22 | 22 | 114 |
| ESS-15LNPT 3.8 | 708.1602.532.20 | L | 315 | 15 | 3/8 | 40.0 | 19 | 27 | 95 |
| ESS-15LNPT 1.2 | 708.1602.534.20 | L | 315 | 15 | 1/2 | 48.0 | 22 | 27 | 109 |
| ESS-18LNPT 1.2 | 708.1602.646.20 | L | 315 | 18 | 1/2 | 47.5 | 22 | 32 | 130 |
| ESS-22LNPT 3.4 | 708.1602.768.20 | L | 160 | 22 | 3/4 | 49.0 | 27 | 36 | 185 |
| ESS-28LNPT 1.1 | 708.1602.850.20 | L | 160 | 28 | 1 | 55.5 | 36 | 41 | 38 |
| ESS-35LNPT 5.4 | 708.1602.944.20 | L | 160 | 35 | 1 1/4 | 62.5 | 46 | 50 | 405 |
| ESS-42LNPT 3.2 | 708.1602.992.20 | L | 160 | 42 | 1 1/2 | 65.0 | 50 | 60 | 570 |

Achtung: Endmontage des vormontierten Schaftes wird erst nach 1/2 Umdrehung der Überwurfmutter über den Punkt des deutlich fühlbaren Kraftanstiegs erreicht.

Schaft vormontiert.

Attention: Final standpipe assembly, the nut will be tightened at least by 1/2 of a turn beyond the point of a noticeable increase in force.

With pre-assembled cutting ring.

Atención: El montaje del vástago premontado se completa girando 1/2 vuelta la tuerca de unión a partir del punto en que aumenta claramente la resistencia.

Vástago premontado.



LEHENGOMAK, S.A.